

Always read entire label before using product



- FEATURES:**
- High resistance to acids and salts
  - Resists high pressure wash off
  - Non DG
  - Non flammable
  - Non Perishing to rubber
  - Non conductive to 70kV
  - Food Grade
  - Biodegradable

**CONTENTS:** Pure industrial grade lanolin

## USAGE EXAMPLES:

- Anti-seize, anti-galling
- Assembly lubricant & rubber grease
- Protects electrical components from moisture including connectors - multi pin plugs
- Prevents galling of stainless steel and aluminium
- Stops electrolysis due to dissimilar metals
- Ideal anti-seize for non grease-able pins (lanolin never dries out).
- Belt dressing
- Metal to metal soft seal gasket
- Drilling & cutting aid
- Welding nozzle dip - non flammable

## APPLICATION:

- Suitable for all wire ropes in highly corrosive environments
- Sub sea applications using hand applied or pressurised systems (eg. Viper)

Timber applications:

- Lubricant for bolts in timber also on timber bearers & end grains & checkouts to stop moisture rot

## CLEANUP:

- Use a biodegradable degreaser such as Lanotec's organic Citra-Force™ or PowaWash™.

## SOME TESTING:

- Torque Coefficient (K Factor) of the lubricant was determined to be 0.15. For further specific testing get in contact with Lanotec
- AS 1580.460.2 - Highly resistant to acid and salt
- AS 2380 Clause 4.2 - Flameproof enclosure - Complies with standard
- AS 2331.3.1 - Neutral Salt Spray (Corrosion)
- High Voltage Testing - dry tested to 70kV - non conductive
- Chemical Analysis - contains no heavy metals
- Meets MIL-C-16173E requirements - Solvent-dispersed corrosion preventative compounds that deposit thin, easily removable films after evaporation of solvent.
- Meets BMS 3-23F requirements - Boeing Material Specification, Organic Corrosion Inhibiting Compounds
- AS 2205.2.1 – 2003 - Weld Test

## APPROVALS:

- HACCP Australia Food Safety Accreditation Systems - Food Grade Lubricant
- NZFSA Approval Lubricant C12
- All Lanotec products are Halal certified by the Taher Accreditation authority.

FOR MORE INFORMATION: Lanotec Australia  
Pty Ltd  
PO Box 360 Archerfield QLD 4108 07 3373 3700  
info@lanotec.com.au

For safe handling of this product, please consult the Safety Data Sheet (SDS)